







English	Français	Deutsch	Italiano	Español
Countersunk head	Tête fraisée	Senkkopf	Testa svasata	Cabeza avellanada
Body: steel Zinc plated Clear trivalent passivated	Corps: Acier Revêtement zingué Passivation claire trivalente	Hülse: Stahl Verzinkt Klar chromatiert, Cr6-frei	Corpo: Acciaio Zincato Passivazione chiara trivalente	Cuerpo: Acero Zincado Pasivado claro trivalente
Stem: carbon boron steel Zinc plated Clear trivalent passivated	Tige: Acier Revêtement zingué Passivation claire trivalente	Dorn: Stahl Verzinkt Klar chromatiert, Cr6-frei	Gambo: Acciaio Zincato Passivazione chiara trivalente	Vástago: Acero Zincado Pasivado claro trivalente



ø nom.					M max.	øB min.	D ₁ max.	T min.	 kN ¹⁾	 kN ¹⁾	Part No/ref
	min.	max.	min.	max.							
4.8 (3/16")	3.17	8.41	4.9	5.1	20.0	8.3	2.2	10.5	6.44	5.11	02761-00615
	3.17	12.22			26.3			13.5			02761-00619
6.4 (1/4")	3.17	12.07	6.6	7.0	26.4	10.1	2.4	12.2	11.78	10.45	02761-00821

all dimensions in mm / en millimètres / alle Maße in mm / in millimetri / en milímetros

1) typical values / valeurs moyennes / typische Werte / Valori tipici / valores típicos

Note:

External stem locking feature requires special nose piece. / Le verrouillage extérieur de la tige nécessite d'un nez spécial. / Die Restdornverriegelung erfordert ein spezielles Mundstück. / Funzione di bloccaggio esterno del gambo richiede particolare nasello. / El bloqueo mecánico del vástago requiere de una sufridera especial.